

Digium® IP Phones

Designed for Asterisk® and Switchvox®



D65

Digium's executive-level feature phone with 6 line keys and a scrolling key for up to 20 pages of rapid dial/busy lamp fields for your most important contacts.

Digium phones are designed exclusively for use with Asterisk and Switchvox. All models include HDVoice and unprecedented plug-and-play deployment at a price that fits any budget. Enhance your users' productivity with built-in advanced applications, including voicemail, call log, contacts, phone status, user presence, parking and queue metrics. Digium phones provide simple, intuitive access to a wealth of information, saving valuable time. With the phones' open, JavaScript API, you can also build customized applications to tailor the user experience to your specific needs. Digium's highly-integrated phones are the only phones that allow you to take full advantage of the flexibility and customization of Asterisk and Switchvox.

D60

Digium's entry-level phone with 2 line keys. This is Digium's best value phone designed for any employee in the company.

D62

Digium's mid-level gigabit phone with 2 line keys. This is Digium's value phone for users who need gigabit connectivity.

HDVoice

	D60 Entry-level	D62 Mid-level	D65 Executive-level
Line Keys	2	2	6
Feature Keys	4	4	4
Rapid Dial/ Busy Lamp Field Keys	Up to 1 key 1 contact	Up to 1 key 1 contact	Up to 5 keys 100 contacts
Ethernet LAN and PC Port	10/100Base-T	10/100/1000Base-T	10/100/1000Base-T
Main Display	4.3 inch, color	4.3 inch, color	4.3 inch, color
Built-in Bluetooth	No	No	■
Power over Ethernet (PoE)	■	■	■
Advanced Phone Applications	■	■	■

Learn more at www.digium.com/phones

Digium IP Phones for Asterisk and Switchvox

General Specifications



D60/D62

User Interface

4.3 inch, 480 x 272 pixel backlit color LCD display
2 line appearance keys
4 feature keys
4 context-sensitive soft keys
6-key navigation controller
Headset, speaker, and mute keys
2-color LED message waiting indicator
Volume control

Connections

2P2C (RJ-9) handset jack
2P2C (RJ-9) headset jack
2 switched 10/100 Mbps Ethernet ports (D60)
2 switched 10/100/1000 Mbps Ethernet ports (D62)
5 volt DC power port

D65

User Interface

4.3 inch, 480 x 272 pixel backlit color LCD display
6 line appearance keys
Rapid dial page scroll key
4 feature keys
4 context-sensitive soft keys
6-key navigation controller
Headset, speaker and mute keys
2-color LED message waiting indicator
Volume control

Connections

2P2C (RJ-9) handset jack
2P2C (RJ-9) headset jack
2 switched 10/100/1000 Mbps Ethernet ports
5 volt DC power port

Phone Applications

Visual Voicemail
Contacts
Presence/Status
Call log
Parked calls
Call queues
Info
Forward calls

Phone Features

Auto-answer
Headset-answer
Headset-ring
Distinctive ring
Custom ringtones
Call waiting
Call transfer (blind & attended)
Call forward
Call hold
Call parking
Call pickup
Intercom / Paging
Message Waiting Indication (MWI)
Busy Lamp Field (BLF)
3-way conferencing
Do Not Disturb (DND)
Redial
Call timer
Caller ID display

Audio Features

Handset, speaker and headset modes
HD speaker
Full-duplex speakerphone with echo cancellation
Hearing aid compatible
Codecs: G.722 ulaw/alaw, G.726, G.729A, iLBC, G.722, Opus, G.722.1 & G.722.1C licensed by Polycom®
Acoustic Echo Cancellation (AEC)
Background noise suppression
Multicast audio playback

Network Support

Static or DHCP IP address assignment
NTP time synchronization
Priority queueing, VLAN, LLDP
NAT traversal
QoS
802.1X pass-through with auto-logout
802.1X authentication

Language Support

English German
French Italian
Portuguese Spanish
Dutch

SIP / VoIP Support

SIP v2
UDP, TCP, TLS transport
DTMF, RFC2833
SIP peer-to-peer
SIP presence (Subscribe/Notify)
Per-account digit map/dial plan
Dial using SIP URI
Dial using SIP server
Secure SIP authentication
SDES Secure RTP (SRTP)

Provisioning

Switchvox
DPMA (Digium Phone Module for Asterisk)
DHCP Option 66
XML Configuration
Phone GUI
Phone UI

Management

Digest authenticated login to phone web UI
Firmware update via browser
Factory restore via GUI
Remote logging via Syslog

Regulatory Compliance

FCC Part 15 Class B
CE Mark
UL 60950

Maximum Power Consumption

D60/D62/D65: 6W

Operating Conditions

Temperature: +32° to 122° F / 0 to 50° C
Relative Humidity: 5% to 95% noncondensing

Storage Temperature

-4 to 160F / -20 to 70C

Size

D60/D62/D65:
7.623 x 9.173 x 1.538 inches /
19.36 x 23.3 x 3.91 cm

Weight

D60/D62/D65:
2 lbs 2.24 oz / 0.97 kg

Warranty

One year

Software Minimum Version Requirements

Switchvox 6.2
DPMA 3.1

Digium, Inc. • www.digium.com

445 Jan Davis Drive NW
Huntsville, AL 35806, USA
+1 256-428-6000

Europe/Africa

South Africa +27 87 550 2590
United Kingdom +44 845 564 1419

Asia Pacific

Australia +61 28 073 4490
New Zealand +64 9 9 51 5875